Valrust 1609 UPC

SECTION I - IDENTIFICATION



Ultrasonic Power Corporation 239 E. Stephenson Street Freeport, IL 61032 (815) 235-6020

•

Product Number RP1609UPC

Product Name Valrust 1609 UPC
Chemical Family Rust Preventive

CAS Number Multiple
Date Prepared 2/13/2023
Revision Number 2/13/2023

Recommended Use Industrial Use Only

SECTION II - HAZARDOUS IDENTIFICATION

GHS CLASSIFICATION:

Classification

Aspiration Hazard Category 2

WARNING!

GHS LABEL:



Hazard Statements

May be harmful if swallowed and enters airways.

Valrust 1609 UPC

Precautionary Statements

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container to an approved waste disposal plant.

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

Component Name	CAS#	Component%	OSHA PEL	ACGIH TLV
Light Naphthenic Hydrotreated	64742-53-6	70 - 100	5mg/m³ (Oil	5mg/m³ (Oil
Distillates			Mist)	Mist)
Acrylic Copolymer	Mixture	5 - 15	Not Established	Not Established
Calcium Sulfonate	61789-86-4	3 - 10	5 mg/m3 (Oil	5 mg/m3 (Oil
			Mists)	Mists)

SECTION IV - FIRST AID MEASURES

Contact with eyes: Flush with water for 15 minutes. Seek medical attention if irritation persists.

Skin contact: Wash exposed areas with water and mild soap. Remove contaminated clothing and

launder before reuse. If irritation persists, seek medical attention.

Inhalation: Remove victim to fresh air. Administer oxygen or artificial respiration if breathing is

affected or stopped. Seek immediate medical attention.

Ingestion: If swallowed. Do not induce vomiting. Seek immediate medical attetntion.

SECTION V - FIREFIGHTING MEASURES

Suitable Extinguishing Media: Water fog, foam, CO2, dry chemical.

Special Fire Fighting Procedures Use self-contained breathing apparatus and full bunker gear in fire areas.

Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water

used for cooling.

Unusual Fire Fighting Hazards: No unusual fire hazards known. Combustible liquid.

Valrust 1609 UPC

SECTION VI - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Keep all sources of ignition and hot metal surfaces away from spill or

release.

Environmental Precautions: Prevent liquid from entering drains, sewers or waterways.

Contain spill if it can be done with minimal risk.

Notify proper authorities.

Methods for Cleaning Up: Using only non-sparking tools and explosion proof equipment, collect

spill on absorbent material and put into approved container.

SECTION VII - HANDLING AND STORAGE

Handling and Storage:

- "Empty" containers retain residue and/or vapor and may be dangerous.
 Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources.
- NFPA Class III B storage.

SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:

Component Name	CAS#	OSHA PEL	ACGIH TLV
Light Naphthenic Hydrotreated Distillates	64742-53-6	5mg/m³ (Oil Mist)	5mg/m³ (Oil Mist)
Acrylic Copolymer	Mixture	Not Established	Not Established
Calcium Sulfonate	61789-86-4	5 mg/m3 (Oil Mists)	5 mg/m3 (Oil Mists)

Engineering Controls: Adequate local or mechanical to reduce vapor or mist to below the PEL or

TLV.

Monitoring: Follow accepted work and hygiene practices for handling combustible

product.

Personal Protective Equipment (PPE)

Eye Protection: Recommend goggles or approved OSHA device with side shields.

Skin Protection: Impervious solvent resistent gloves.

Impervious apron and work boots recommend where splashing may occur.

Respiratory Protection: Use the proper respirator in areas devoid of proper ventilation, and the

chemical exposure is above the OSHA PEL or ACGIH TLV.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Valrust 1609 UPC

Appearance	Amber Liquid
Odor	Mild Petroleum
pH@25°C	N/A
Melting/Freezing Point	N/Av
Flashpoint	300°F, COC
Specific Gravity	0.8921
Solubility	Negligible
Auto-Ignition Temperature	N/Av
Decomposition Temperature	N/Av
VOC Content	< 1.0 %
Odor Threshold	N/Av
Boiling Range	380 - 600°F
Evaporation Point	N/Av (Butyl Acetate=1)
Flammable Limits - Upper	N/Av
Flammable Limits - Lower	N/Av
Vapor Pressure	<1 mm Hg @ 20°C
Vapor Density (Air=1)	>1 (Air=1)
Viscosity	14.5 cSt @ 40°C

Stability: Stable

Conditions to Avoid: Extreme heat and ignition sources.

Hazardous Decomposition/Byproducts: CO, CO2, and various hydrocarbons under combustion

conditions.

Hazardous Polymerization: Will not occur.

Polymerization Conditions to Avoid: None

Incompatibilities: Stong oxidizers

Valrust 1609 UPC

SECTION XI - TOXICOLOGICAL INFORMATION

Likely Route of Exposure: Contact and inhalation; ingestion possible.

Inhalation: May cause irritation to the upper respiratory tract and CNS depression.

Eye Contact: May cause eye irritation including stinging, watering and redness which

may result in corneal injury.

Skin Contact: Contact may cause mild skin irritation including redness, burning and

drying/cracking of the skin.

Ingestion: Aspiration hazard. Can enter the lungs during swallowing or vomiting

and cause chemical pneumonia and edema.

Acute Toxicity Value: See Health Hazards below.

Chronic (Long Term) Effects: See Health Hazards above.

Toxicity:

Component Name	LD50	LC50
Light Naphthenic Hydrotreated Distillates	Not Established	Not Established
Acrylic Copolymer	Not Established	Not Established
Calcium Sulfonate	> 20 g/kg in Rats	Not Established

Reproductive Effects Not Applicable

Teratogenicity Not Applicable

Mutagenicity Not Applicable

Embryotoxicity Not Applicable

Sensitization to Product Not Applicable

Synergistic Products Not Applicable

Carcinogenicity Not Listed as a Carcinogen

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicity: Information not available.

Valrust 1609 UPC

Mobility: Information not available.

Degradability: Information not available.

BioAccumulation: Information not available.

SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Follow Federal, state, and local regulations.

SECTION XIV - TRANSPORT INFORMATION

DOT SHIPPING INFORMATION

Proper Shipping Name: Not Regulated

Contains:

Hazard Class and Label: Identification Number: Packaging Group: Other Shipping Info:

SECTION XV - REGULATORY INFORMATION

TSCA STATUS:..... The components of this product are listed on the TSCA Inventory

SARA TITLE III SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCE:

No chemicals in this material are subject to the reporting requirements.

SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

Acute	Chronic	Fire	Pressure	Reactive
N/A	N/A	N/A	N/A	N/A

SARA TITLE III SECTION 313 SUPPLIER INFORMATION:

No chemicals in this material are subject to the reporting requirements.

CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:

Valrust 1609 UPC

No chemicals in this material are subject to the reporting requirements.

CALIFORNIA PROPOSITION 65:

No chemicals in this material are subject to the reporting requirements.

SECTION XVI - OTHER INFORMATION

Additional: